

INSTALLATION INSTRUCTIONS

IMPORTANT SAFETY INSTRUCTIONS

MESURES DE SECURITE A RESPECTURE

Before assembling your ACCESS LIGHTING fixture, please make sure that you carefully read through this instruction sheet. Save this instruction sheet and refer to it when additions to or changes in the fixture configuration are made.

Lisez attentivement ce manuel d'instructions. Enregistrer cette feuille d'instructions et de s'y référer lorsque les ajouts ou changements dans la configuration de montage sont faites.

CONSULT A QUALIFIED ELECTRICIAN TO ENSURE CORRECT BRANCH

CONSULTER UN ELECTRICIEN QUALIFIE POUR VOUS ASSURER QUE LES CONDUCTEURS DE LA DERIVATION SONT ADEQUATS

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

CE PRODUIT DOIT ETRE INSTALLE SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAIT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHERENTS

NOTE: The important safeguards and instructions that appear in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that can't be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture. Read all instructions

Do not install this fixture in hazardous locations.

N'installez pas cet appareil dans des emplacements dangereux. Do not install any fixture assembly closer than 6 inches from any curtain or similar combustible material.


Laisser une distance d'au moins 6 pouces entre ce luminaire et la toute surface combustible.

"WARNING Risk of Fire and Electric Shock."

"CAUTION: Risque d' Incendie et de Choc Electriques."

GENERAL INFORMATION

All electrical connections must be in accordance with all ordinances, Local and the U.S. National Electrical Codes (NEC). These fixtures are intended for mounting to a standard 4" metal octagon outlet box. The box must be directly supported by the building structure and U.L. Recognized.



COLLECTION

APPLICATION

SOLERO

Ceiling

MODEL NO.

20464LEDD 20465LEDD 20466LEDD 20467LEDD

WHAT YOU NEED

by Electrical Code

Wiring Supplies as Specified

• Screwdriver

Wire Cutters

WHAT WE PROVIDE


- Mounting Hardware
- 1 x Acrylic Shade
- 1 x Metal frame
- IFD


Recommended Dimmers

Lutron DVCL-153P (Diva) Lutron TGCL-153P (Adriani/ Toggler) Lutron SCL-153P (Skylark) Leviton 6672-1L_ (Decora Sureslide) _ indicates color finish Leviton 6674-POW (Decora Sureslide) Cooper AAL06-C_ (AL Smart dimmer)_ indicates color finish Cooper DAL06P-C_ (AL Decorator dimmer)_ indicates color finish Cooper SAL06P-C_ (AL Smart dimmer master)_ indicates color finish

STEP BY STEP INSTRUCTIONS

Before starting your installation disconnect the Power by turning off the Circuit Breaker or by removing the fuse at the fuse box. Just turning the light off at the light switch is not sufficient to prevent electrical shock.







PREPARE FIXTURE


If there is an existing fixture remove it. Expose the supply wires from the J-box . Connect the black supply wire to the black fixture wire. Secure with the supplied wire nut. Connect the white supply wire to the white fixture wire. Secure with the supplied wire nut. Either wrap the green wire around one of the protruding screws or connect it to the supply ground wire. Secure all wires with U.L. Certified electrical tape (not supplied). Tuck all wires carefully into the J-Box.

MOUNT THE CROSSBAR

Mount the crossbar up to the J-box. Secure with the supplied screws.

MOUNT THE FIXTURE

Mount the fixture canopy up to the crossbar. Secure with the supplied screw knobs. Place metal frame over the acrylic shade and hold up to the canopy aligning the holes with the threaded rods. Secure with the supplied nuts.



RESTORE THE ELECTRICITY AND CHECK THE OPERATION OF YOUR NEW ACCESS LIGHTING FIXTURE

