

Anton LED Flush Mount ANF Series

Features

This modern single drum design provides a dramatic look and features Lumafuse™ laminated fabric/acrylic shade. White bottom acrylic diffuser disperses the light.

Construction

The canopy is made of 22-gauge cold rolled steel. The LED pan is white painted. The acrylic diffuser is supported by the inner shade. Power supply connections must be made inside a junction box (not included).

Finish

Stamped metal components are paintable white baked gloss enamel.

Diffuser

Utilizing Lumafuse™ laminated fabric to acrylic. Available in Jute and Linen White. Matte white acrylic bottom lay-in diffuser.

Electrical

Input 120-277 VAC 60 HZ. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120VAC.

LED

Integrated LED modules capable of producing: 12" - 18W - 1400 source lumens 15" - 30W - 2400 source lumens 19" - 42W - 3200 source lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for damp locations.


Options (Consult Factory)

Semi-flush mount Battery back-up

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.



Ordering Information:

	Source								
Jute	Linen White	LED	Lumens	Adjustable CCT	DIA.	D			
ANF1214LAJUD-JT	ANF1214LAJUD-LW	18W	1400	3000K/3500K/4000K	12-1/4"	4-3/4"			
ANF1524LAJUD-JT	ANF1524LAJUD-LW	30W	2400	3000K/3500K/4000K	15"	5-1/2"			
ANF1932LAJUD-JT	ANF1932LAJUD-LW	42W	3200	3000K/3500K/4000K	19-1/4"	5-1/2"			

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	



3in1 color temperature

3000K/3500K/4000K



Jute

Linen White