

Clark Outdoor LED Sconce CLKW Series

LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANITY FIXTURE TYPE

Features

All purpose LED sconce with photocell is an energy saving long-lasting alternative to Incandescent. Integrated photocell for dust-to-dawn operation, uses only 9 watts of power to operate. Excellent use in cold climates. LEDs turn on instantly at full brightness. Ideal use for security and general lighting. Provides lighting in residential, commercial, retail and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Die-cast aluminum with a durable powder coat. Power supply connections must be made inside a junction box (not included).

Finish

All exposed metal surfaces are coated in black powder finish.

Diffuser

Clear glass panels.

Electrical

Input 120 VAC/60 Hz .05A Operating temperature -20° C (-4°F) to 40° C (104° F) Not compatible with dimmers.

LED

Integrated LED (DOB) modules capable of producing: 6W, 450 source lumens, 3000K.
Rated for 50,000 Hrs., 80 CRI.

Certification

cETLus certified for outdoor wet locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

		Source				
Black	LED	Lumens	CCT	Н	W	D
CLKW450L30BK	6W	450	3000K	11-1/2"	6-1/2"	8-1/8"



