

PRODUCT DESCRIPTION

Cylinders of White cased glass are mounted onto a cast aluminum frame of Satin Nickel or Polished Chrome. LED modules evenly illuminate and provide soft yet ample illumination. Multi volt input is standard which allows for installation into commercial applications.

MEASUREMENTS

DIMENSION : 18" L 4.75" H x 3.5" Ext **BACK PLATE** : 7" W x 4.75" H x 2.25" HCO

HANGING WEIGHT : 1.788 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 1,140 Rated (880 Del.)

BULB : 1 x 12W LED PCB Integrated , 12W Total

BULB INCLUDED : (Integrated) DIMMABLE : Triac CL CRI : 90 CRI COLOR_TEMP : 3000K LIGHTING_DIRECTION: Up/Down

FINISHES OPTION



GLASS

White WT

MATERIAL

Aluminum + Glass

RATINGS

CETLUS Damp Location **Energy Star** JA8 ListedADA











ADDITIONAL

INSTALL UP/DOWN: Both RATED LIFE 50000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)

253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com