

CHESTERFIELD

Bridge Style Kitchen Faucet with Sidespray

Features

- Solid brass construction
- Bridge-style brass valve bodies
- Quarter-turn washerless ceramic disc valve cartridges
- ADA compliant traditional cross handles
- Swivel spout assembly with integral diverter assembly
- Solid brass pull-out sidespray assembly
- 6-9/16" (16.7 cm) spout height at outlet
- 8-1/2" (21.6 cm) min. to 10-3/8" (26.4 cm) max. spout reach (c-c)
- For 8" (20.3 cm) centers Maximum 9-3/4" (24.9 cm)
- 1.8 gallons (6.8 liters) per minute maximum flow rate

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- IPC
- NSF 61
- ADA
- ICC/ANSI A117.1
- Energy Policy Act of 1992

9452-1





Colors / Finishes

• 10B: Oil Rubbed Bronze

15: Polished Nickel

• 15S: Satin Nickel - PVD

• 26: Polished Chrome

• Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model Model **Description** Colors | Finishes 9452-1 Bridge Style Kitchen Faucet with Sidespray 10B 15 15S 26 Other

Product Specification: Add "Color / Finish" suffix to Model number, below.

The Bridge Style Kitchen Faucet with Sidespray shall be made of solid brass construction. Faucet shall incorporate a swivel spout assembly with integral side-spray diverter assembly and feature bridge-style brass valve bodies with quarter-turn washerless ceramic disc valve cartridges. Faucet shall have a 1.8 gallons (6.8 liters) per minute maximum flow rate. Product shall be for 8" (20.3 cm) centers - Maximum 9-3/4" (24.8 cm). Product shall incorporate a 6-9/16" (16.7 cm) spout height at outlet and an 8-1/2" (21.6 cm) min. to 10-3/8" (26.4 cm) max. spout reach (c-c). Faucet shall incorporate ADA compliant traditional cross handles. Bridge-Style Kitchen Faucet with Sidespray shall be Newport Brass Model 9452-1/__

9452-1

PRODUCT DIMENSIONS (Units are in inches)



