### PRODUCT DESCRIPTION

Lamp holder suitable for applications requiring higher wattage lamp sources. Construction is minimal with a short adjustment bracket connecting high heat rated socket with contact head.

### FEATURES

- · White glazed porcelain bare socket
- · Heat resistant teflon coated wire lead
- · Low profile mounting / adjustment arm
- · High strength stainless steel electrical contacts
- One or two circuit track capable
- · Accepts LED lamps

## CONSTRUCTION

Adjustment Arm: 0.080" Rigid steel "L-bracket" connects fixture housing to electrical contact head. Screw locks angle position to prevent loss of angle from constant heat exposure.

#### ELECTRICAL SYSTEM

Voltage: 120V input Socket: Medium base Lamp: R/PAR20, BR/PAR30 or BR40/PAR38 (not included) Wattage: 150W max.

#### **ONE/TWO CIRCUIT CONVERSION**

Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT- 2300 series two-circuit track.

#### LABELS AND LISTINGS

UL Listed





Project

Catalog No.


# Notes

# PRODUCT IMAGES AND DIMENSIONS



shown with shown with PAR20

shown with PAR38



PAR30

# **Universal Lamp Holder**

Catalog No.	Finish	Adapter
NTH-115	W = White	(blank) = H-style
		/J = J-style
		/L = L-style

Example: NTH-115W = Universal Lamp Holder, White finish, H-Style Adapter

IN G

6505 Gayhart Street, Commerce, CA 90040 Tel 800.686.6672 | www.noralighting.com | e-mail: nora@noralighting.com © 2020 Nora Lighting, Inc. All rights reserved. Specifications subject to change without notice.