

| Project:      |  |  |
|---------------|--|--|
| Fixture Type: |  |  |
| Location:     |  |  |
| Contact:      |  |  |

# 14IN LED DC CTC

Wall or Ceiling mounted • Damp location listed PROGRESS LED



## **Description:**

14" LED flush mount with etched white opal acrylic diffuser with a clean modern look. 3000K color temperature and 90+ CRI. Acrylic bowl is attached with a twist and lock action for ease of installation. This fixture can be mounted on ceiling or wall. ENERGY STAR rated. Brushed Nickel finish.

## P350077-009-30

#### Images:

## **Specifications:**

- Brushed Nickel (-009) (plated)
- Steel Construction
- White Acrylic diffuser
- · Etched white opal acrylic diffuser.
- · Acrylic bowl is attached with a twist and lock action.
- · Can be mounted on ceiling or wall.
- · Dimmable to 10% with many ELV dimmers
- · Acrylic diffuser twists into the frame so there are no exposed fasteners for a clean modern look.
- · 2002 lumens,77 lumen/watt (delivered)
- · 3000K color temperature, 90CRI
- Energy Star Qualified
- Meets California T24 JA8-2016.
- Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- · ENERGY STAR® qualified
- Meets California Title 24 JA8-2016



#### **Performance:**

| Number of Modules      | 1                                  |
|------------------------|------------------------------------|
| Input Power            | 26w                                |
| Input Voltage          | 120 V                              |
| Input Frequency        | 60 Hz                              |
| Lumens/LPW (Delivered) | 2002/77 (LM-79)                    |
| ССТ                    | 3000 K                             |
| CRI                    | 90 CRI                             |
| Life (hours)           | 36,000 (L70/TM-21)                 |
| FCC                    | FCC Title 47, Part 15, Class B     |
| Min. Start Temp        | -30 °C                             |
| Max. Operating Temp    | 30°C                               |
| Warranty               | 5 year warranty                    |
| Labels                 | UL Damp location listed            |
|                        | ENERGY STAR® qualified             |
|                        | Meets California Title 24 JA8-2016 |
|                        |                                    |

#### **Dimensions:**

Diameter: 14" Height: 4-3/4"



# 14IN LED DC CTC





P350077-009-30

## **Dimming Notes:**

P350077 is designed to be compatible with many Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron NTEVL-300 Lutron DVELV-300P Lutron DVCL-253P Lutron Caseta Wireless Lutron AYCL-153P Lutron TGCL-153-PH Lutron NTLV-600 Lutron MAELV-601 Lutron N-600 Leviton 6674

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.